



# PRODUCT DATA SHEET

SKSHU PAINT CO., LTD.

## ForestCoat Exterior Wall Sealer SS579

### SGGD001

#### PRODUCT INFORMATION

<b>PRODUCT NAME</b>	ForestCoat Exterior Wall Sealer SS579
<b>Code</b>	SS579
<b>DESCRIPTION</b>	<p>3TREES ForestCoat Exterior Wall Sealer adopts high-quality raw materials and automatic production procedure. The advanced technologies improve the wall coverage, strengthen the ability of anti-alkali, and protect the topcoat from the erosion of chemicals inside the wall.</p> <p>Complies with SS579:2015 Specification for Water-Based Sealer.</p>
<b>APPLICATION AREA</b>	Suitable for exterior wall applications as a primer/sealer for coating systems.
<b>FEATURES</b>	<ul style="list-style-type: none"><li>❖ Good adhesion</li><li>❖ Alkali resistant</li><li>❖ Peeling resistant</li><li>❖ Easy application</li><li>❖ Non-added lead &amp; mercury</li><li>❖ Environmentally friendly paint certified under the Singapore Green Building Product Certification Scheme</li></ul>
<b>PACK SIZE</b>	20L
<b>COLOUR</b>	Off White
<b>FINISH</b>	Matt
<b>COMPOSITION (nominal)</b>	Modified Acrylic Emulsion, Pigment and Filler, Additives and Water.
<b>STORAGE</b>	Containers should be thoroughly sealed and conserved in cool, dry and well-ventilated places with temperature between 5 to 35°C to prevent product deterioration caused by the impurity substance.

#### APPLICATION

<b>APPLICATION METHOD</b>	Rolling, spraying, brushing.
<b>PAINT PREPARATION</b>	<p>Add 0-10% of water, stir evenly and let stand for 5 minutes.</p> <p>The specific dilution ratio can be determined according to the application method and practice.</p>
<b>DRYING TIME</b> <i>Thinning</i>	<p>Touch dry: 1 H/25°C.</p> <p>Recoat time: 2-4 H/25°C.</p> <p>Dry time varies according to the differences of the temperature and humidity of the application environment.</p>
<b>ENVIRONMENTAL REQUIREMENT</b>	Temperature $\geq 5$ °C ; Humidity <85%.
<b>THEORETICAL COVERAGE</b>	<p>11-13 m<sup>2</sup>/L per coat (dry film thickness 30µm)</p> <p>The actual consumption is subject to the application method, the hardness, dryness and roughness of substrate and application environment.</p>
<b>CLEANING UP</b>	Clean all equipment with clean water immediately after use.



# PRODUCT DATA SHEET

SKSHU PAINT CO., LTD.



Application method    Touch dry 1 hour    Cleaning

## PRE-APPLICATION

### SURFACE PREPARATION

The base layer is required to be solid, dry, smooth, clean, and free of dust or grease. Surfaces such as concrete, cement plaster, asbestos, and caulking bricks must be properly treated to remove all foreign objects and loose surfaces. The primer must be applied evenly according to the recommended coverage rate. Check the moisture content and pH value of the primer putty before applying the primer. The moisture content should be less than 10% and the pH less than 10.

### RECOMMENDED APPLICATION SYSTEM

PUTTY (2 COATS):  
3TREES Exterior Wall Putty  
PRIMER (1 COAT):  
3TREES ForestCoat Exterior Wall Sealer SS579  
FINISH (2 COATS):  
3TREES ForestCoat Exterior Paint SS345

This system consists of SS579 sealer and SS345 exterior paint for external wall applications.

## PRECAUTION

### HEALTH, SAFETY AND ENVIRONMENT INFORMATION

Construct in a well-ventilated condition and do not breathe in vapour or spray.  
Use suitable personal protection equipment.  
Use wet sanding/flattening wherever possible.  
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Avoid damage environmental balance.  
Collect spillage.  
Keep away from food, drinks, animal feed and children.  
Store in a cool and shaded place.  
Container must be in a secure, upright position and be tightly closed.  
Wash immediately with soap and water or a proprietary skin cleaner if contact with skin.  
Dispose of any paint waste in accordance with the appropriate Environmental Quality Regulations.

For further details on Material Safety Data Sheet, kindly contact:

SKSHU Paint Co., Ltd.

#518 Liyuan North Avenue, Licheng District, Putian, Fujian, China

Tel: 0086-400-8823-777    E-mail: [info@3treespaint.com](mailto:info@3treespaint.com)    Website: [www.3treespaint.com](http://www.3treespaint.com)

*Note:* Please follow the instructions for use. The actual situation may be slightly different due to environmental, substrate and temperature, etc. If you have any questions, please do not hesitate to contact your local agent or regional manager. The technical data is only for reference, and SKSHU Paint Co., Ltd. reserves the right to introduce and modify the information without further notice.